

APPLICATIONS

Economy 5" & 6" Recessed downlight retrofit solution with integrated LED power supply and thermal management system combined in a single compact unit designed to fit most standard 5" & 6" recessed cans.

FEATURES

- Long life LEDs with up to 50,000 hours at 70% lumen maintenance.
- Choice of 2700K, 3000K, 4000K or 5000K color temperatures with 80 CRI.
- Uses 1.18W high power, high quality LEDs
- Dimmable to 10% with most dimmers
Save 75% compared to incandescent sources
- High efficiency driver with a power factor $\geq .90$ with input power of 120V, 50-60Hz
- Built-in LED Driver
- Power consumption of 12 watts
- Operation temperature of -20°C -40°C (-4°F -104°F)
- Easy installation with adjustable torsion spring
- Torsion spring is designed to fit into 5" or 6" housing automatically without changing mounting tab
- No tools required for installation

WARRANTY & LISTINGS

- Tested in accordance with IESNA LM79 & LM80
- ETL Listed for wet location
- ENERGY STAR® qualified
- Passes FCC Class B
- ROHS Compliant
- 5-year warranty on all electronics and housing




SILVER AND WHITE BAFFLE OPTION






OPTIONAL TRIM FACE

- CLRD6-12XX-SQT-WH
Square (snap)
- CLRD6-12XX-RND-SL
Silver (snap)



DIMENSIONS



HOUSING

- Compatible with most 5" and 6" housings
- Compatible with insulated, non-insulated, and air-tight ceilings
- Durable thermoplastic construction
- E26 medium screw-base Edison connector provides easy retrofit of incandescent housings
- **6" square baffle snap-in (options)**

PRODUCT PARAMETER

MODEL	OPTIONS	LUMINAIRE WATTS	LUMINAIRE LUMENS	LUMENS PER WATT	TITLE 24	COLOR TEMPERATURE
CLRD6-1227-RND-WH	BW WHITE BAFFLE	12	900	75	NO	2700K
CLRD6-1230-RND-WH	BW WHITE BAFFLE	12	960	80	NO	3000K
CLRD6-1240-RND-WH	BW WHITE BAFFLE	12	1000	83	NO	4000K
CLRD6-1250-RND-WH	BW WHITE BAFFLE	12	1060	88	NO	5000K